2008 Scheduled Maintenance Intervals

Miles (in thousands)	5/25/45/65/85/105	15/55/95	35/75
Kilometres (in thousands)	8/40/70/100/130/160	25/85/145	55/115
Engine Oil – change oil and replace filter			
Wiper Blades – check condition and replace if necessary			
Wiper/Washer/Headlight Washer – check adjustment and function,			
add fluid if necessary			
Tires and Spare – check for wear and damage, check pressure			
 check for wear and damage, check pressure and renewal 			
date of tire set (where applicable)			
Tires – rotate	5K only		
Service Reminder Display – reset			
Brake System – check for damage, leaks, pad thickness, fluid level			
Cooling System – check level, add if necessary			
Exhaust System – check for damage, leaks			
Engine On Board Diagnostics – check fault memory		Except Audi Q7, TT, A5, S5, R8	Except Audi Q7, TT, A5, S5, R8
Engine Compartment – check for leaks			
Battery – check and replace if necessary			
Dust and Pollen Filter – replace			
Automatic Transmission and Final Drive – check for leaks			
Manual Transmission and Final Drive – check for leaks			
Haldex Clutch – change oil			A3, TT only
Front Axle – check for excessive play, check dust seals on ball joints and		Except Audi Q7, TT, A5, S5, R8	
tie rod ends		11, A5, S5, K8	
Lights – check all lights, check headlight adjustment		A8, S8 only	Except Audi Q7, TT, R8, A5, S5
Drive Shaft Boots – check			
Doors – lubricate doors, check straps and hood latch		A8, S8 only	
Spark Plugs – replace at 35,000 miles or 3 years, whichever occurs first.			35K only: A3 3.2L, TT 3.2L, A8 6.0L
Then, every 40,000 miles or 3 years, whichever occurs first.			11 3.2L, A6 6.UL
– replace at 55,000 miles or 6 years, whichever occurs first.		55K only: except	
Then, every 60,000 miles or 6 years, whichever occurs first.		A3 3.2L, TT 3.2L, A8 6.0L	
– replace at 75,000 miles			75K only: A3 3.2L, TT 3.2L, A8 6.0L
Continuously Variable Transmission (multitronic) – change ATF			
Power Steering Fluid – check, add if necessary			
Air Cleaner – clean housing, replace filter element		55K only: except	35K only: RS 4, A8 6.0L 75K only: RS 4, Audi Q7
		RS 4, Aúdi Q7 4.2L, A8 6.0L	4.2L, A8 6.0L
Ribbed V Belt and Tensioner – check condition and replace if necessary		RS 4, R8 only	RS 4, Audi Q7 3.6L, A8 6.0L, R8 only
Ribbed V Belt – replace			75K only: S4
– check condition and replace if necessary. Check tension of			75K only: 2.0L, 3.2L, 4.2L FSI, 5.2L
belt drive with manual tensioner and retension if necessary.			
Snow Screen for Air Cleaner – clean		A4, A5, S5 and A6 only	A4, A5, S5 and A6 only
Underbody – check for damage and leaks		,	
Road Test – check braking, kick-down, steering, electrical, heating and ventilation			
systems, air conditioning, ASL Automatic Shift Lock and power accessories			
Rear Lid Hinges – lubricate		A8, S8 only	A8, S8 only
Horn – check function			
Br ake Discs – check thickness			
Lights – c heck all lights via instrument cluster. Check license			Audi Q7, TT, A5, S5, R8 only
plate light from the rear of the vehicle			55, No only
Interior Lights – check all interior lights, glove box illumination,			
control lights and MMI (if applicable)			

At 110K miles (175km) replace timing belt (2.0L engine only). Check condition of timing belt tensioning system, dampening pulleys, and idler pulleys and replace if necessary (2.0L engine only). Brake Fluid – replace every 2 years regardless of mileage.

 $Cloth Top-check function and rollover protection every 2 years \, regardless \, of \, mileage \, (Audi \, A4 \, Cabriolet, S4 \, Cabriolet \, and \, RS \, 4 \, Cabriolet \, only).$