

2010 Scheduled Maintenance Intervals

| Miles (in thousands) | 5/25/45/65/85/105/125 | 15/55/95 | 35/75/115 |
|---|---|---|--|
| Kilometers (in thousands) | 8/40/70/100/130/160/190 | 25/85/145 | 55/115/175 |
| Engine Oil/Oil Filter – change oil and replace filter | | | |
| AdBlue Fluid – fill completely with fresh fluid (maximum capacity: 23 liters) and adapt learned values for AdBlue tank under guided fault finding after filling fluid | Audi Q7 3.0L TDI only | Audi Q7 3.0L TDI only | Audi Q7 3.0L TDI only |
| Cooling System – check level, add if necessary | | | |
| Engine On-Board Diagnostics – check fault memory | | A3, A6, S6, A8 only | A3, A6, S6, A8 only |
| Engine Compartment – check for leaks | | | |
| Battery – check and replace if necessary | | | |
| Dust and Pollen Filter – replace | | | |
| Spark Plugs – replace at 35,000 miles or 3 years, whichever occurs first. Thereafter, every 40,000 miles or 3 years, whichever occurs first. | | | A4 2.0L TFSI, A5 2.0L TFSI only |
| – replace at 55,000 miles or 6 years, whichever occurs first. Thereafter, every 60,000 miles or 6 years, whichever occurs first. | | 55K only; except A4 2.0L TFSI, A5 2.0L TFSI | |
| Power Steering Fluid – check, add if necessary | | | |
| Air Cleaner – clean housing, replace filter element | | 55K only; except Audi Q7 4.2L | 75K only: Audi Q7 4.2L only |
| Ribbed V Belt and Tensioner – check condition and replace if necessary | | R8 only | Audi Q7 3.6L, R8 only |
| Ribbed V Belt – check condition, replace if necessary. Check tension of belt drive with manual tensioner and retension if necessary. | | | 75K only: V6 FSI, V6 TFSI (rear belt), 2.0L TFSI, 5.2L V10 FSI, 4.2L V8 FSI only |
| – replace only the V belt for the compressor drive | | | 75K only: 3.0L TFSI only |
| Snow Screen for Air Cleaner – clean | | A4, S4, A5, S5 and A6 only | A4, S4, A5, S5 and A6 only |
| Fuel Filter – remove water | | Audi Q7 3.0L TDI only | |
| – replace | | 55K only: A3 2.0L TDI only | Audi Q7 3.0L TDI only 115K only: A3 2.0L TDI |
| Diesel Particulate Filter (DPF) – check ash loading according to manufacturer's work procedure, replace* if necessary. | USA: 125K only: Audi Q7 3.0L TDI, A3 2.0L TDI only Canada: 200,000 km only: Audi Q7 3.0L TDI, A3 2.0L TDI only | | |
| Plenum Panel – remove cover for plenum panel to check water drain and clean if necessary | | except A3, Audi Q5 | except A3, Audi Q5 |
| Tires and Spare Wheel – check for wear and damage, check tire pressure, reset Tire Pressure Monitoring System (TPMS) | | | |
| – check for wear and damage, check tire pressure and renewal date of tire repair set (where applicable), reset Tire Pressure Monitoring System (TPMS) | | | |
| Tires – rotate, reset TPMS | 5K only | | |
| Wiper Blades – check condition and replace if necessary | | | |
| Wiper/Washer/Headlight Washer – check adjustment and function, add fluid if necessary | | | |
| Lights – check all lights, check headlight adjustment | | A8 only | A3, A6, S6, A8 only |
| Lights – check all lights via instrument cluster. Check license plate light from the rear of the vehicle | | | Audi Q7, A4, S4, Audi Q5, TT, A5, S5, R8 only |
| Interior Lights – check all interior lights, glove box illumination, control lights and MMI (if applicable) | | | |
| Doors – lubricate doors, check straps and hood latch | | A8 only | Except A8 |
| Rear Lid Hinges – lubricate | | A8 only | A8 only |
| Service Reminder Display – reset | | | |
| Horn – check function | | | |
| Brake System – check for damage, leaks, pad thickness, fluid level | | | |
| Brake Discs – check thickness | | | |
| Exhaust System – check for damage, leaks | | | |
| Front and Rear Axle – check for excessive play, check dust seals on ball joints and tie rod ends | | A3, A6, S6, A8 only | |
| Drive Shaft Boots – check | | | |
| Automatic Transmission and Final Drive – check for leaks | | | |
| Manual Transmission and Final Drive – check for leaks | | | |
| Continuously Variable Transmission (multitronic) – change ATF | | | |
| Haldex Clutch – change oil | | | A3, TT only |
| DSG/S Tronic – change oil and replace filter element | | | A3, TT only |
| Underbody – check for damage and leaks | | | |
| Road Test – check braking, kick-down, steering, electrical, heating and ventilation systems, air conditioning, ASL Automatic Shift Lock, power accessories and reset driver information display | | | |
| Timing Belt – replace at 110K miles (175,000 km) on Audi TT 2.0T with front-wheel drive or 130K miles (205,000 km) on Audi A3 2.0L TDI only. Check condition of timing belt tensioning system, dampening pulleys, and idler pulleys and replace if necessary. | | | |
| Brake Fluid – replace every 2 years regardless of mileage. | | | |
| Cloth Top – check function and rollover protection every 2 years regardless of mileage (Audi A5/S5 Cabriolet only). | | | |

*If DPF replacement is not necessary, perform check every 20,000 miles (30,000 km) thereafter until replacement becomes necessary. Subsequent DPF replacement interval is a minimum of 120,000 miles (200,000 km), thereafter.